


8-Port 10/100/1000Mbps with 4-Port PoE Gigabit Ethernet Switch



Centralized Power Distribution for Gigabit Ethernet Networking

To fulfill the demand of sufficient PoE power for network applications with Gigabit speed transmission, PLANET has come out with a new member in the 802.3af PoE Gigabit Ethernet Switch family - GSD-804P, the 8-Port 10/100/1000Mbps with 4-Port 802.3af Power over Ethernet Switch which features high performance Gigabit IEEE 802.3af PoE (Up to 15.4 watts) and totally 55 watts PoE budget on half of the 10/100/1000Mbps TP ports of GSD-804P. The four 802.3af PoE ports provide PoE power injector function which is able to drive 4 IEEE 802.3af compliant powered devices. The GSD-804P also provides a simple, cost-effective and non-blocking wire-speed performance with 10-inch metal shape for desktop deployment in compact housing, SOHO office or department network application.



Lead PoE Device into High-Speed Generation of Gigabit Ethernet

Providing data transfer and PoE the GSD-804P can reduce the need of extension cables and electrical outlets on the wall, ceiling or any unreachable place. It helps to lower the installation costs and simplify the installation effort. Besides, the key feature is energy saving. With more efficient switching power supply, the efficiency of the GSD-804P would be much better than four linear power adapters in the long run. Furthermore, it is the ideal device for bridging among Fast Ethernet and Gigabit Ethernet workgroups and networks. With Gigabit throughput and four 802.3af PoE interfaces supported, the GSD-804P is ideal for small business and workgroups to efficiently deploy the PoE network for the wireless access points, IP-based surveillance camera or IP phones in any places.

RJ-45 Interface

- 8-Port 10/100/1000Mbps Gigabit Ethernet ports
- 4-Port supports 48V DC power to PoE Powered Device

PoE

- Complies with IEEE 802.3af Power over Ethernet End-Span PSE
- Up to 4 IEEE 802.3af devices powered
- Supports PoE Power up to 15.4 watts for each PoE port
- Auto detects powered device (PD)
- Circuit protection prevents power interference between ports
- Remote power feeding up to 100m

Switching

- Hardware based 10/100/1000Mbps Auto-negotiation and Auto MDI/MDI-X
- Flow control for full duplex operation and back pressure for half duplex operation
- Integrates address look-up engine, supporting 8K absolute MAC addresses
- 9K Jumbo Frame supports at all speed (10/100/1000Mbps)
- Automatic address learning and address aging

Hardware

- 10-inch desktop size, rack mountable; 1U height
- LED indicators for PoE ready and PoE activity
- Optional Rack Ear Accessories Kit for 10-inch cabinet (RKE-10A) and 19-inch cabinet (RKE-10B)
- 1 silent fan to provide stable and efficient power performance
- Energy-Saving technology
- Link down power saving
- Intelligent scales power based on cable length

Excellent Ethernet Traffic Transmission Ability

The GSD-804P features high performance switch architecture capable of providing the non-blocking 16Gbps switch fabric and wire-speed throughput as high as 11.9Mpps, which greatly simplifies the tasks of upgrading the LAN for catering to increasing bandwidth demands. Besides, the 802.3x Full-Duplex flow control function of the GSD-804P enables PD devices and servers directly connect to the Switch for wire-speed packet transfer performance without risk of packet loss.

Energy-Saving

The GSD-804P uses new engine that provides energy saving up to 40% less energy than the normal switch and remains the superior performance. The GSD-804P incorporates two advanced Green Networking technologies:

- Idle Mode Link Down power saving
- Intelligent Scales Power based on cable length

The Idle mode Link Down power saving of the GSD-804P complies with IEEE 802.3az Energy Efficient Ethernet (EEE) standard to automatically lower power for a given port when it is not linked. The Intelligent Scales Power technology actively determines the appropriate power level based on the cable length. When connecting to the GSD-804P with Ethernet cable shorter than 20m, a device can obtain maximum power saving because the GSD-804P would automatically detect the Ethernet cable length and reduce power usage. The connected device can substantially reduce overall power consumption, which makes a significant contribution to energy saving.


Easy Cable Connection

All RJ-45 copper interfaces in the GSD-804P support 10/100/1000Mbps Auto-Negotiation for optimal speed detection through RJ-45 Category 6, 5 or 5e cables. It also supports standard Auto-MDI/MDI-X that can detect the type of connection to any Ethernet device without requiring special straight or crossover cables.

Applications

Department / Workgroup PoE Switch

Providing 4-Port PoE in-line power interface, the GSD-804P can easily build a power centrally-controlled IP phone system, IP camera system and wireless AP group for the enterprise. For instance, up to 4 cameras can be installed around the corner in the company for surveillance demands or up to 4 wireless APs to build a wireless roaming environment in the office. Without the power-socket limitation, the Switch makes the installation of cameras or wireless AP more easier and more efficiently.



Specifications

Model	GSD-804P	
Hardware Specifications		
Network Connector	8-Port RJ-45 for 10/100/1000Base-T	
PoE Inject Port	4-Port with 802.3af PoE injector function, Port-1 to Port-4	
LED Display	1 Power , 1 Fan Alert 1-4 port PoE in-use 1-8 port Speed, LNK/ACT	
Switch Architecture	Store and Forward switch architecture	
MAC Address	8K MAC address table with auto learning function	
Switch Fabric	16Gbps	
Switch Throughput	11.9Mbps	
Jumbo Packet Size	9K Bytes	
Power Requirements	AC 100~240V, 50/60Hz, 1.5A	
Power Consumption	Max. 65 watts / 221 BTU	
Dimensions (W x D x H)	217 x 135 x 43 mm	
Weight	890g	
Power over Ethernet		
PoE Standard	IEEE 802.3af Power over Ethernet / PSE	
PoE Power Supply Type	End-Span	
PoE Power Output	Per Port 48V DC, 350mA . Max. 15.4 watts	
Power Pin Assignment	1/2(+), 3/6(-)	
PoE Power Budget	55 watts	
Standard Conformance		
EMI Safety	FCC Class A, CE	
Operating Temperature	0 ~ 50 degrees C	
Storage Temperature	-40 ~ 70 degrees C	
Operating Humidity	5 ~ 95%, relative humidity, non-condensing	
Storage Humidity	5 ~ 95%, relative humidity, non-condensing	
Standard Compliance	IEEE 802.3	Ethernet
	IEEE 802.3u	Fast Ethernet
	IEEE 802.3ab	Gigabit Ethernet
	IEEE 802.3x	Flow Control
	IEEE 802.3af	Power over Ethernet

Ordering Information

GSD-804P	8-Port 10/100/1000Mbps with 4-Port PoE Gigabit Ethernet Switch
----------	--

Accessories

RKE-10A	Rack-mount Kit for 10-inch Cabinet
RKE-10B	Rack-mount Kit for 19-inch Cabinet